
K9R022/3NS2



recessed luminaire • round

Application : General office area’s, General healthcare area’s

housing: heat sink in extruded aluminium

light source : LED • 5000 K

optics : lens • acrylic (PMMA)

Lumen output in emergency mode : 220 lm

function: anti-panic lighting

monitoring: EST+ self-test

photobiological safety: EN 62471: RISK GROUP 1 UNLIMITED

Product information

Mechanical properties

dimensions : 30 mm x 32 mm

cut-out size : 24 mm x 32 mm

colour: RAL9003-signalwhite

IP: IP20

IK: IK04

ambient temperature: 5°C - 35°C •

Electrical properties

power : 0.9 W

voltage: 220-230V

frequency : 50-60Hz AC

Battery

mode of operation : non-maintained

Battery: 4 x NiMh 1,2V 2,2Ah


autonomy : 180 minutes

ETAP tomorrow's light


This document has been compiled by ETAP with the greatest possible care. However, the information contained in this publication is not binding and may change due to technical development. ETAP is not liable for any damage whatsoever resulting from the use of this document.
www.etaplighting.com // Made in Belgium

Luminance

luminous flux : 220 lm



Distance tables: ceiling mounted



AP Ceiling for 0.5 Lux and 220 lm

H (m)	a	b	c	d
2.6	5.1	12.4	5.2	12.4
2.8	---	13.2	5.4	13.2
3.0	5.6	13.9	5.7	13.9
3.5	6.1	15.7	6.2	15.7
4.0	6.6	17.3	6.6	17.3
4.5	3.7	17.5	3.7	17.5
5.0	1.2	14.8	1.2	14.8
6.0	---	15.0	---	15.0
7.0	---	15.4	---	15.4
8.0	---	16.2	---	16.2
10.0	12.3	4.6	11.1	4.6

ETAP tomorrow's light

This document has been compiled by ETAP with the greatest possible care. However, the information contained in this publication is not binding and may change due to technical development. ETAP is not liable for any damage whatsoever resulting from the use of this document.
www.etaplighting.com // Made in Belgium

AP Ceiling for 1.0 Lux and 220 lm

H (m)	a	b	c	d
2.6	4.5	11.5	4.5	11.5
2.8	4.7	12.1	4.7	12.1
3.0	3.3	12.8	3.3	12.8
3.5	0.9	10.5	0.9	10.5
4.0	0.5	10.6	0.6	10.6
4.5	0.2	10.5	0.1	10.5
5.0	0.1	10.9	---	10.9
6.0	---	11.7	---	11.7
7.0	8.9	3.3	8.1	3.3

Available accessories

K9RH85X1 *Adaptation plate for K5 renovation (RAL9003)*


K9RH85X2 *Adaptation plate for K5 renovation (RAL9006)*

K9RH5 *Test button set*

ETAP tomorrow's light

This document has been compiled by ETAP with the greatest possible care. However, the information contained in this publication is not binding and may change due to technical development. ETAP is not liable for any damage whatsoever resulting from the use of this document.
www.etaplighting.com // Made in Belgium

Dimensional drawing



This document has been compiled by ETAP with the greatest possible care. However, the information contained in this publication is not binding and may change due to technical development. ETAP is not liable for any damage whatsoever resulting from the use of this document.
www.etaplighting.com // Made in Belgium