

K133/3S2



surface-mounted luminaire for wall mounting • linear

Application : General healthcare area's, Playing fields

housing: impact-resistant polycarbonate

light source : LED • 6000 K

optics : diffuser • polycarbonate (PC)

Lumen output in emergency mode : 45 lm

function: single-sided signage

monitoring: ESM - wired

photobiological safety: EN 62471: RISK GROUP 0
UNLIMITED

Product information

Mechanical properties

dimensions : 304 mm x 155 mm x 73 mm

colour: RAL9018 - papyrus white

IP: IP42

IK: IK04

ambient temperature: 5°C - 35°C •

Electrical properties

power : 1.5 W

voltage: 220-230V

frequency : 50-60Hz AC

Battery

mode of operation : adjustable: non-maintained/maintained

Battery: 4 x NiMh 1,2V 1,1Ah

autonomy : 180 minutes

Luminance

luminous flux : 45 lm

distance of perception : 26

distance of perception : 26

Available accessories

K1H1 *Recessed mounting frame*

K1H2 *Right angle wall bracket*

K1H3 *Parallel wall bracket*

K1H5-50 *Suspension set*

K1H7 *Protective grille*

K1H14 *Adaptation plate for K8 renovation*

K1H15 *Adaptation plate for old K2 8renovation*

K1H16 *Adaptation plate for old K2 13W renovation*

K1H17 *Adaptation plate for old K1 renovation*

K1H8 *Optional template for recessed mounting set*

K1H10 *Mounting plate for mounting on rough surfaces*

K1H11 *Accessory for through wiring and/or surface mounted cabling*

Dimensional drawing

