K9R143/1-AX1



surface-mounted luminaire • linear

Application : General office area’s, General healthcare area’s

housing: powder coated die-cast zamak

light source : LED • 5000 K

optics : sign plate with dot-matrix • acrylic (PMMA)

Lumen output in emergency mode : 80 lm

function: double sided signage

monitoring: ESM - wired

photobiological safety: EN 62471: RISK GROUP 0 UNLIMITED

Product information

Mechanical properties

dimensions : 324 mm x 26 mm x 63 mm

colour: RAL9003 - white (textured)

IP: IP42

IK: IK04

ambient temperature: 5°C - 35°C •

Electrical properties

power : 2.5 W

voltage: 220-230V

frequency : 50-60Hz AC

Battery

mode of operation : adjustable: non-maintained/maintained

Battery: 4 x NiMh 1,2V 1,1Ah

autonomy : 90 minutes


ETAP tomorrow's light

This document has been compiled by ETAP with the greatest possible care. However, the information contained in this publication is not binding and may change due to technical development. ETAP is not liable for any damage whatsoever resulting from the use of this document.
www.etaplighting.com // Made in Belgium

Luminance


luminous flux : 80 lm

distance of perception : 24



distance of perception : 24

Isolux diagram - wall mounting




Available accessories

K9RH4-50X1 *Suspension set (RAL9003-white)*

This document has been compiled by ETAP with the greatest possible care. However, the information contained in this publication is not binding and may change due to technical development. ETAP is not liable for any damage whatsoever resulting from the use of this document.
www.etaplighting.com // Made in Belgium

Dimensional drawing



This document has been compiled by ETAP with the greatest possible care. However, the information contained in this publication is not binding and may change due to technical development. ETAP is not liable for any damage whatsoever resulting from the use of this document.
www.etaplighting.com // Made in Belgium