


D42R1/LEDW3540D



recessed luminaire • round

Application : General office area's, General education area's

housing: lacquered aluminium

light source : LED • 3000 K

optics : LED+LENS™ • polycarbonate (PC) lens • wide-angle

UGR classification : <=22

luminous flux: 4250 lm

luminous efficacy : 121 lm/W

LLMF: 98% @ 50khrs (Tq=25°C)

Product information

Mechanical properties

dimensions : 250 mm x 71 mm

cut-out size : 230 mm x 71 mm

colour: RAL9003 - signal white

trim: flat trim

type : individual luminaire

IP: IP20

Electrical properties

driver: DALI dimmable

power : 35 W

voltage : 220-240V

frequency : 50-60Hz AC

photobiological safety : EN 62471: RISK GROUP 1 UNLIMITED

current : 12 A

Luminance


luminous flux : 4250 lm

luminous efficacy : 121 lm/W

UGR classification =: <=22

luminous area : 0.04 m²

Average Luminances (Cd/m²) for 4250lm					
Gamma	C0	C30	C45	C60	C90
45°	30138	30138	30138	30138	30138
50°	12960	12960	12960	12960	12960
55°	6505	6505	6505	6505	6505
60°	4089	4089	4089	4089	4089
65°	3116	3116	3116	3116	3116
70°	2643	2643	2643	2643	2643
75°	2298	2298	2298	2298	2298
80°	1975	1975	1975	1975	1975
85°	1555	1555	1555	1555	1555



Classifications

CIE: 835 / 982 / 997 / 1000 / 1000

CIE FLUXCODE : 0.84 / 0.98 / 1.00 / 1.00 / 1.00

BZ: BZ1

CAE: Symmetrical

DIN: A60 (Nach Arbeitsblatt 7)

DIN_U: Phi u = 1.00

DIN_SU: Phi su = 0.76

UTE: 1.00 B + 0.00 T



This document has been compiled by ETAP with the greatest possible care. However, the information contained in this publication is not binding and may change due to technical development. ETAP is not liable for any damage whatsoever resulting from the use of this document.
www.etaplighting.com // Made in Belgium

Lifetime Data (Tq=25.0°C)

Time(khrs)	LLMF(%)	Cx(%)
10	100	2
20	99	4
30	99	6
40	99	8
50	98	10
60	98	12

Luminous intensities in cd

Intensity for 4250lm

Gamma	C0	C45	C90
0°	2578.1	2578.1	2578.1
5°	2538.0	2538.0	2538.0
10°	2511.1	2511.1	2511.1
15°	2545.8	2545.8	2545.8
20°	2601.6	2601.6	2601.6
25°	2597.7	2597.7	2597.7
30°	2475.9	2475.9	2475.9
35°	2113.7	2113.7	2113.7
40°	1451.0	1451.0	1451.0
45°	738.1	738.1	738.1
50°	288.5	288.5	288.5
55°	129.2	129.2	129.2
60°	70.8	70.8	70.8
65°	45.6	45.6	45.6
70°	31.3	31.3	31.3
75°	20.6	20.6	20.6
80°	11.9	11.9	11.9
85°	4.7	4.7	4.7
90°	1.4	1.4	1.4

UGR classification =

Corrected Glare Ratings for a Total Lamp Flux of 4250lm (S = 0.25H)

	Room Reflection Factors (%)									
	Ceiling	Walls	Floor	70	70	50	50	30	30	30
	70	70	50	50	30	70	70	50	50	30
	50	30	50	30	30	50	30	50	30	30
	20	20	20	20	20	20	20	20	20	20
Room Dimensions	Viewed Crosswise					Viewed Endwise				
X = 2H Y = 2H	20.7	22.2	21.0	22.5	22.7	20.7	22.2	21.0	22.5	22.7
Y = 3H	20.6	21.9	20.9	22.2	22.5	20.6	21.9	20.9	22.2	22.5
Y = 4H	20.5	21.8	20.9	22.0	22.3	20.5	21.8	20.9	22.0	22.3
Y = 6H	20.5	21.6	20.8	21.9	22.2	20.5	21.6	20.8	21.9	22.2
Y = 8H	20.4	21.5	20.8	21.8	22.2	20.4	21.5	20.8	21.8	22.2
Y = 12H	20.4	21.4	20.8	21.8	22.1	20.4	21.4	20.8	21.8	22.1
X = 4H Y = 2H	20.5	21.7	20.8	22.0	22.3	20.5	21.7	20.8	22.0	22.3
Y = 3H	20.4	21.4	20.8	21.8	22.1	20.4	21.4	20.8	21.8	22.1
Y = 4H	20.4	21.3	20.8	21.6	22.0	20.4	21.3	20.8	21.6	22.0
Y = 6H	20.4	21.1	20.8	21.5	21.9	20.4	21.1	20.8	21.5	21.9
Y = 8H	20.3	21.1	20.8	21.5	21.9	20.3	21.1	20.8	21.5	21.9
Y = 12H	20.3	21.0	20.7	21.4	21.8	20.3	21.0	20.7	21.4	21.8
X = 8H Y = 4H	20.3	21.0	20.7	21.4	21.8	20.3	21.0	20.7	21.4	21.8
Y = 6H	20.3	20.9	20.7	21.3	21.8	20.3	20.9	20.7	21.3	21.8
Y = 8H	20.3	20.8	20.7	21.3	21.7	20.3	20.8	20.7	21.3	21.7
Y = 12H	20.2	20.7	20.7	21.2	21.7	20.2	20.7	20.7	21.2	21.7
X = 12H Y = 4H	20.3	20.9	20.7	21.4	21.8	20.3	20.9	20.7	21.4	21.8
Y = 6H	20.2	20.8	20.7	21.2	21.7	20.2	20.8	20.7	21.2	21.7
Y = 8H	20.2	20.7	20.7	21.2	21.7	20.2	20.7	20.7	21.2	21.7
UGR Variations with Observer Position for Luminaire Spacings S										
S = 1.0H	+2.8		-6.6		+2.8		-6.6			
S = 1.5H	+5.1		-8.2		+5.1		-8.2			
S = 2.0H	+7.1		-8.9		+7.1		-8.9			

Colour properties

Correlated Colour Temperature : 3000

Ra: CRI (Ra) 80

Efficiency

Utilisation Factors according to IES (%)										
	Room Reflection Factors (%)									
Ceiling	80	80	80	50	50	50	30	30	30	0
Walls	50	30	10	50	30	10	50	30	10	0
Floor	20	20	20	20	20	20	20	20	20	0
RCR = 1	109	107	106	103	101	100	99	98	97	92
2	100	96	94	95	92	90	92	89	88	83
3	91	87	83	87	83	81	85	81	79	75
4	84	78	74	80	76	73	78	74	72	68
5	77	71	67	74	69	66	72	68	65	62
6	71	65	60	69	63	60	67	62	59	56
7	66	59	55	64	58	54	62	57	54	52
8	61	55	50	59	54	50	58	53	49	47
9	57	50	46	55	50	46	54	49	45	43
10	53	47	42	52	46	42	51	45	42	40

Utilisation Factors according to LiTG (%)										
	Room Reflection Factors (%)									
Ceiling	80	80	80	50	50	50	50	50	30	0
Walls	50	30	50	30	50	30	50	30	30	0
Floor	30	30	10	10	30	30	10	10	10	0
k = 0.60	65	58	62	56	63	57	61	56	55	50
0.80	77	70	72	67	74	68	71	66	66	61
1.00	85	77	79	73	81	75	77	72	72	67
1.25	94	88	86	82	90	84	84	81	80	76
1.50	99	93	90	86	94	89	88	85	84	80
2.00	106	100	95	91	99	95	92	90	89	85
2.50	111	106	98	95	103	99	95	93	92	88
3.00	115	110	100	98	106	103	98	96	95	91
4.00	118	114	102	100	108	106	99	98	96	93
5.00	121	117	103	102	110	108	100	99	98	94

Dimensional drawing

