


E21/LED5N075S



surface-mounted luminaire • linear

Application : Harsh environments

housing: lacquered aluminium

light source : LED • 4000 K

optics : linear lens • polycarbonate (PC) • medium wide-angle

UGR classification : <=25

luminous flux: 7450 lm

luminous efficacy : 133 lm/W

LLMF: 97% @ 50khrs (Tq=25°C)

Product information

Mechanical properties

dimensions : 1370 mm x 80 mm x 135 mm

colour: RAL7035 - light grey

type : individual luminaire

IP: IP66, IP69K

IK: IK07

ambient temperature: -25°C - 35°C (Optional: -35°C - 60°C) •

Electrical properties

driver: not dimmable

power : 56 W

voltage : 220-240V

frequency : 50-60Hz AC

photobiological safety : EN 62471: RISK GROUP 1 UNLIMITED

Luminance


luminous flux : 7450 lm

luminous efficacy : 133 lm/W

UGR classification =: <=25

luminous area : 0.08 m²

Gamma	Average Luminances (Cd/m²) for 7450lm				
	C0	C30	C45	C60	C90
45°	11483	15694	22494	28532	38153
50°	8278	10823	16142	24697	35602
55°	6371	7971	11432	19591	32746
60°	5005	6256	8444	14769	28813
65°	4201	5009	6576	10851	23798
70°	3470	4298	5429	8092	18550
75°	3040	3748	4560	6187	13863
80°	2845	3286	4018	4913	9707
85°	2723	3036	3589	4011	4710



Classifications

CIE: 607 / 867 / 954 / 983 / 1002

CIE FLUXCODE : 0.62 / 0.88 / 0.97 / 0.98 / 1.00

BZ: BZ2/1/BZ3/1.25/BZ2/1.5/BZ3

CAE: CAE 3/5°/CAE 2/55°/CAE 3

DIN: A50 (Nach Arbeitsblatt 7 und 8)

DIN_U: Phi u = 0.98

DIN_SU: Phi su = 0.64

UTE: 0.98 C + 0.02 T



This document has been compiled by ETAP with the greatest possible care. However, the information contained in this publication is not binding and may change due to technical development. ETAP is not liable for any damage whatsoever resulting from the use of this document.
www.etaplighting.com // Made in Belgium

Lifetime Data (Tq=25.0°C)

Time(khrs)	LLMF(%)	Cx(%)
10	99	2
20	99	4
30	98	6
40	98	8
50	97	10
60	96	12

Luminous intensities in cd

Intensity for 7450lm

Gamma	C0	C45	C90	Gamma	C0	C45	C90
0°	3761.8	3761.8	3761.8	90°	105.0	92.5	1.7
5°	3726.0	3716.1	3732.8	95°	88.7	67.9	0.1
10°	3604.4	3663.8	3665.9	100°	82.0	52.6	0.0
15°	3369.5	3490.9	3555.8	105°	71.7	39.6	0.1
20°	3191.2	3259.6	3396.2	110°	56.9	29.9	0.0
25°	2996.1	3089.8	3231.3	115°	44.2	22.6	0.0
30°	2625.5	2916.9	3041.4	120°	33.6	16.2	0.0
35°	2243.4	2538.5	2814.1	125°	24.0	10.6	0.0
40°	1501.9	2221.1	2540.0	130°	16.6	5.8	0.0
45°	971.1	1730.0	2228.7	135°	10.9	0.4	0.0
50°	674.1	1180.6	1890.5	140°	5.6	0.0	0.0
55°	494.9	786.6	1551.6	145°	0.1	0.0	0.1
60°	367.0	540.1	1190.1	150°	0.0	0.0	0.1
65°	287.5	385.4	830.9	155°	0.0	0.0	0.1
70°	218.6	286.8	524.1	160°	0.0	0.0	0.2
75°	173.6	212.7	296.4	165°	0.1	0.0	0.1
80°	144.5	161.1	139.3	170°	0.8	0.6	0.4
85°	120.0	119.3	33.9	175°	1.9	1.7	1.4
90°	105.0	92.5	1.7	180°	1.8	1.8	1.8

UGR classification =

Corrected Glare Ratings for a Total Lamp Flux of 7450lm (S = 0.25H)

	Room Reflection Factors (%)									
Ceiling	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor	20	20	20	20	20	20	20	20	20	20
Room Dimensions	Viewed Crosswise					Viewed Endwise				
X = 2H Y = 2H	18.2	19.8	18.6	20.1	20.4	23.8	25.4	24.2	25.7	26.0
Y = 3H	18.6	20.0	18.9	20.4	20.7	24.7	26.2	25.1	26.5	26.8
Y = 4H	18.7	20.1	19.1	20.5	20.8	25.0	26.3	25.3	26.7	27.0
Y = 6H	18.9	20.2	19.3	20.6	20.9	25.1	26.3	25.5	26.7	27.0
Y = 8H	19.0	20.3	19.4	20.6	21.0	25.1	26.3	25.5	26.7	27.0
Y = 12H	19.1	20.3	19.6	20.7	21.1	25.0	26.2	25.5	26.6	27.0
X = 4H Y = 2H	18.8	20.2	19.2	20.5	20.9	23.7	25.1	24.1	25.4	25.7
Y = 3H	19.3	20.5	19.7	20.9	21.2	24.7	25.9	25.1	26.3	26.6
Y = 4H	19.6	20.6	20.0	21.0	21.4	25.1	26.1	25.5	26.5	26.9
Y = 6H	19.9	20.8	20.3	21.2	21.6	25.3	26.2	25.7	26.6	27.0
Y = 8H	20.0	20.9	20.5	21.3	21.8	25.3	26.2	25.8	26.6	27.0
Y = 12H	20.2	21.0	20.7	21.4	21.9	25.3	26.1	25.8	26.5	27.0
X = 8H Y = 4H	19.8	20.7	20.3	21.1	21.6	25.0	25.9	25.5	26.3	26.8
Y = 6H	20.3	21.0	20.8	21.5	21.9	25.3	26.0	25.8	26.5	27.0
Y = 8H	20.5	21.1	21.0	21.6	22.1	25.4	26.0	25.9	26.5	27.0
Y = 12H	20.8	21.3	21.3	21.8	22.4	25.4	26.0	25.9	26.5	27.0
X = 12H Y = 4H	19.9	20.7	20.3	21.1	21.6	25.0	25.8	25.5	26.2	26.7
Y = 6H	20.4	21.0	20.9	21.5	22.0	25.3	25.9	25.8	26.4	26.9
Y = 8H	20.6	21.2	21.2	21.7	22.2	25.4	25.9	25.9	26.4	27.0
	UGR Variations with Observer Position for Luminaire Spacings S									
S = 1.0H	+1.0		-1.0			+0.2		-0.3		
S = 1.5H	+1.4		-1.5			+0.7		-0.9		
S = 2.0H	+2.2		-1.9			+1.9		-2.0		

Colour properties

Correlated Colour Temperature : 4000


Ra: CRI (Ra) 80

Efficiency

Utilisation Factors according to IES (%)										
	Room Reflection Factors (%)									
Ceiling	80	80	80	50	50	50	30	30	30	0
Walls	50	30	10	50	30	10	50	30	10	0
Floor	20	20	20	20	20	20	20	20	20	0
RCR = 1	105	103	101	98	96	95	94	93	91	86
2	94	89	86	88	84	82	84	81	79	74
3	84	78	73	79	74	71	76	72	69	65
4	75	69	64	71	66	62	69	64	61	57
5	68	61	56	65	59	55	63	58	54	51
6	62	55	50	59	53	49	58	52	48	45
7	57	50	45	55	48	44	53	47	43	41
8	53	45	40	50	44	40	49	43	39	37
9	49	41	37	47	40	36	46	40	36	34
10	45	38	33	44	37	33	42	37	33	31

Utilisation Factors according to LiTG (%)										
	Room Reflection Factors (%)									
Ceiling	80	80	80	50	50	50	50	50	30	0
Walls	50	30	50	30	50	30	50	30	30	0
Floor	30	30	10	10	30	30	10	10	10	0
k = 0.60	55	47	52	46	53	46	51	45	44	38
0.80	67	58	62	56	63	56	60	55	54	48
1.00	75	66	70	63	71	64	67	62	61	55
1.25	85	76	77	72	79	73	75	70	69	63
1.50	91	83	82	77	85	79	79	75	74	68
2.00	98	91	88	83	91	86	85	81	79	74
2.50	104	98	92	88	96	91	89	85	84	79
3.00	109	103	95	92	100	96	92	89	87	83
4.00	113	108	98	95	103	99	94	92	90	85
5.00	117	112	100	98	106	103	96	94	92	88

Dimensional drawing



E2*/LED2*	620 mm
E2*/LED4*	1120 mm
E2*/LED6*	1620 mm