

D90/LEDW20DEX1

recessed luminaire • round

application : Office, Healthcare, Education, Horeca, Retail, Leisure

housing: polycarbonate

light source : LED module • 3000 K

optics : Reflector and lens • Polycarbonate (PC) with aluminium thin film, satin look • wide-angle

UGR classification : <=19

luminous flux: 2050 lm

luminous efficacy : 113 lm/W

LLMF: 98% @ 50khrs (Tq=25°C)



Mechanical properties

dimensions : 190 mm x 100 mm

cut-out size : 175 mm x 100 mm

colour: RAL9003 - signal white

trim: flat trim

type : individual luminaire

IP: IP20

Luminance

luminous flux : 2050 lm

luminous efficacy : 113 lm/W

luminance @ 65° : 1000 cd/m²

UGR classification: <=19

luminous area : 0.02 m²

Electrical properties


driver: DALI dimmable, with daylight sensor ELS

power : 18.1 W

voltage : 220-240V

frequency : 50-60Hz AC/DC

photobiological safety : EN 62471: RISK GROUP 1 UNLIMITED



Average Luminances (Cd/m²) for 2050lm

Gamma	C0	C30	C45	C60	C90
45°	20644	20644	20644	20644	20644
50°	10192	10192	10192	10192	10192
55°	1821	1821	1821	1821	1821
60°	191	191	191	191	191
65°	37	37	37	37	37
70°	3	3	3	3	3
75°	0	0	0	0	0
80°	0	0	0	0	0
85°	0	0	0	0	0

D90/LEDW20DEX1

Classifications

CIE: 900 / 1000 / 1000 / 1000 / 1000

CIE FLUXCODE : 0.90 / 1.00 / 1.00 / 1.00 / 1.00

BZ: BZ1

CAE: Symmetrical

DIN: A60 (Nach Arbeitsblatt 7)

DIN_U: Phi u = 1.00

DIN_SU: Phi su = 0.81

UTE: 1.00 A + 0.00 T

Luminous intensities in cd

Lifetime Data (Tq=25.0°C)

Time(khrs)	LLMF(%)	Cx(%)
10	100	2
20	100	4
30	99	6
40	99	8
50	99	10
60	99	12

Intensity for 2050lm

Gamma	C0	C45	C90
0°	1656.8	1656.8	1656.8
5°	1627.0	1627.0	1627.0
10°	1567.3	1567.3	1567.3
15°	1557.0	1557.0	1557.0
20°	1535.2	1535.2	1535.2
25°	1425.9	1425.9	1425.9
30°	1228.6	1228.6	1228.6
35°	907.0	907.0	907.0
40°	520.1	520.1	520.1
45°	279.0	279.0	279.0
50°	125.2	125.2	125.2
55°	20.0	20.0	20.0
60°	1.8	1.8	1.8
65°	0.3	0.3	0.3
70°	0.0	0.0	0.0
75°	0.0	0.0	0.0
80°	0.0	0.0	0.0
85°	0.0	0.0	0.0
90°	0.0	0.0	0.0

UGR classification

Corrected Glare Ratings for a Total Lamp Flux of 2050lm (S = 0.25H)

Ceiling Walls Floor	Room Reflection Factors (%)									
	70	70	50	50	30	70	70	50	50	30
	50	30	50	30	30	50	30	50	30	30
	20	20	20	20	20	20	20	20	20	20
Room Dimensions	Viewed Crosswise					Viewed Endwise				
X = 2H Y = 2H	18.9	20.3	19.2	20.6	20.8	18.9	20.3	19.2	20.6	20.8
Y = 3H	18.8	20.0	19.1	20.3	20.5	18.8	20.0	19.1	20.3	20.5
Y = 4H	18.7	19.8	19.0	20.1	20.4	18.7	19.8	19.0	20.1	20.4
Y = 6H	18.6	19.7	19.0	20.0	20.3	18.6	19.7	19.0	20.0	20.3
Y = 8H	18.6	19.6	18.9	19.9	20.2	18.6	19.6	18.9	19.9	20.2
Y = 12H	18.5	19.5	18.9	19.8	20.2	18.5	19.5	18.9	19.8	20.2
X = 4H Y = 2H	18.7	19.8	19.0	20.1	20.4	18.7	19.8	19.0	20.1	20.4
Y = 3H	18.6	19.5	18.9	19.8	20.2	18.6	19.5	18.9	19.8	20.2
Y = 4H	18.5	19.3	18.9	19.6	20.0	18.5	19.3	18.9	19.6	20.0
Y = 6H	18.4	19.1	18.8	19.5	19.9	18.4	19.1	18.8	19.5	19.9
Y = 8H	18.4	19.0	18.8	19.4	19.8	18.4	19.0	18.8	19.4	19.8
Y = 12H	18.3	18.9	18.8	19.4	19.8	18.3	18.9	18.8	19.4	19.8
X = 8H Y = 4H	18.4	19.0	18.8	19.4	19.8	18.4	19.0	18.8	19.4	19.8
Y = 6H	18.3	18.9	18.7	19.3	19.7	18.3	18.9	18.7	19.3	19.7
Y = 8H	18.2	18.7	18.7	19.2	19.7	18.2	18.7	18.7	19.2	19.7
Y = 12H	18.2	18.6	18.7	19.1	19.6	18.2	18.6	18.7	19.1	19.6
X = 12H Y = 4H	18.3	18.9	18.8	19.4	19.8	18.3	18.9	18.8	19.4	19.8
Y = 6H	18.2	18.7	18.7	19.2	19.7	18.2	18.7	18.7	19.2	19.7
Y = 8H	18.2	18.6	18.7	19.1	19.6	18.2	18.6	18.7	19.1	19.6
UGR Variations with Observer Position for Luminaire Spacings S										
S = 1.0H	+3.7		-16.0		+3.7		-16.0			
S = 1.5H	+6.4		-36.1		+6.4		-36.1			
S = 2.0H	+8.4		-48.5		+8.4		-48.5			

D90/LEDW20DEX1

Colour properties

Correlated Colour Temperature : 3000

Ra: 80

Efficiency

Utilisation Factors according to IES (%)

	Room Reflection Factors (%)									
	80	80	80	50	50	50	30	30	30	0
Ceiling	80	80	80	50	50	50	30	30	30	0
Walls	50	30	10	50	30	10	50	30	10	0
Floor	20	20	20	20	20	20	20	20	20	0
RCR = 1	110	109	107	104	103	102	100	99	98	93
2	102	99	96	97	94	92	94	92	90	85
3	94	90	87	90	87	84	87	85	82	78
4	87	82	78	84	80	77	81	78	75	72
5	81	75	71	78	73	70	76	72	69	66
6	75	69	65	73	68	64	71	67	64	61
7	70	64	60	68	63	59	67	62	59	56
8	65	59	55	64	58	55	62	58	54	52
9	61	55	51	60	54	51	59	54	50	49
10	57	51	47	56	51	47	55	50	47	45

Utilisation Factors according to LiTG (%)

	Room Reflection Factors (%)									
	80	80	80	50	50	50	50	50	30	0
Ceiling	80	80	80	50	50	50	50	50	30	0
Walls	50	30	50	30	50	30	50	30	30	0
Floor	30	30	10	10	30	30	10	10	10	0
k = 0.60	71	65	68	63	69	64	67	62	62	58
0.80	82	75	77	72	79	73	75	71	71	67
1.00	89	82	83	78	85	80	81	77	77	72
1.25	98	92	90	86	94	89	88	85	85	81
1.50	103	97	93	90	97	93	91	89	88	84
2.00	109	104	97	95	102	99	95	93	92	88
2.50	113	108	100	98	105	102	97	96	94	91
3.00	117	113	102	100	108	106	100	98	97	94
4.00	119	116	103	102	110	107	100	99	98	94
5.00	122	119	104	103	112	110	102	101	99	96

Dimensional drawing

