


E4401/LED1W030D



industrial luminaire • linear

Application : Industry ? Production area, Industry ? Warehouse

housing: lacquered aluminium

light source : LED • 3000 K

optics : DUAL?LENS • polycarbonate (PC) • asymmetric

luminous flux: 3150 lm

luminous efficacy : 117 lm/W

LLMF: 96% @ 50khrs (Tq=25°C)

Product information

Mechanical properties

dimensions : 1000 mm x 60 mm x 135 mm

colour: RAL9016 - traffic white

type : in-line mounting: intermediate luminaire

IP: IP40

IK: IK06

Electrical properties

driver: DALI dimmable

power : 27 W

voltage : 220-240V


frequency : 50-60Hz AC

photobiological safety : EN 62471: RISK GROUP 1
UNLIMITED

Luminance

luminous flux : 3150 lm

luminous efficacy : 117 lm/W



Luminous intensities in cd

Intensity for 3150lm											
Gamma	C0	C45	C90	C135	C180	Gamma	C0	C45	C90	C135	C180
0°	1314.7	1314.7	1314.7	1314.7	1314.7	90°	0.0	0.0	0.0	0.0	0.0
5°	1258.1	1163.3	1279.2	1228.9	1253.9	95°	151.1	82.9	4.7	38.6	48.8
10°	1284.0	1265.4	1250.3	1169.4	1207.2	100°	152.0	62.4	5.2	31.1	41.6
15°	1296.3	1234.5	1205.5	1102.5	1129.1	105°	152.2	56.6	5.8	27.8	36.2
20°	1305.6	1179.8	1158.7	1051.7	1048.5	110°	173.9	51.9	6.3	24.8	33.3
25°	1286.3	1135.8	1082.0	978.8	876.9	115°	161.6	48.3	6.8	22.3	30.1
30°	1349.7	1132.4	987.2	830.4	638.1	120°	120.1	43.1	7.1	19.8	27.6
35°	1466.8	1117.7	863.2	641.5	437.9	125°	82.6	35.7	7.3	18.9	26.0
40°	1543.8	1118.0	718.6	441.9	296.8	130°	59.6	29.6	7.5	18.7	24.9
45°	1441.9	1087.5	568.2	326.9	216.7	135°	42.9	24.6	7.8	18.8	24.3
50°	1200.0	950.3	438.4	223.6	159.0	140°	31.7	20.3	7.8	18.6	23.1
55°	826.2	713.1	333.5	162.2	121.5	145°	24.7	17.1	8.2	17.4	21.3
60°	580.5	492.4	247.9	127.6	100.3	150°	19.6	14.4	8.1	15.9	18.9
65°	423.4	335.8	180.4	98.4	84.1	155°	16.1	12.7	8.3	14.1	16.5
70°	335.9	250.1	142.7	79.3	74.6	160°	13.4	11.4	8.4	12.6	14.0
75°	277.7	186.2	104.0	64.4	65.2	165°	11.4	9.9	8.4	11.0	12.2
80°	242.9	142.8	64.4	52.2	55.8	170°	10.1	9.4	8.5	9.8	10.5
85°	179.6	108.1	17.1	40.6	46.3	175°	9.3	8.7	8.5	9.1	9.5
90°	0.0	0.0	0.0	0.0	0.0	180°	8.7	8.7	8.7	8.7	8.7

Colour properties

Correlated Colour Temperature : 3000

Ra: CRI (Ra) 80



Available accessories

E7H301 *Connector (1 per line), 5 or 7 pole, per piece*

E4H1000 *Line end piece, per piece*

E4H111 *Single mounting bracket for ceiling mounting*

E4H112 *Double mounting bracket for ceiling mounting*

E4H121 *Single mounting bracket for threaded rod*

E4H122 *Double mounting bracket for threaded rod*

E4H131 *Single mounting bracket for chain*

E4H141 *Single mounting bracket for steel wire*

E4H142 *Double mounting bracket for steel wire*

E4H132 *Double mounting bracket for chain*

E4H103 *Alignment bracket*

