

CERTIFICATE

(1) Type Examination

(2) Product intended for use in potentially explosive atmospheres - Directive 2014/34/EU

(3) Type Examination Certificate Number: **DEKRA 19ATEX0070 X** Issue Number: **1**

(4) Product: **Emergency Luminaires, Series KE2../6....-ATEX1**

(5) Manufacturer: **ETAP Lighting International NV**

(6) Address: **Antwerpsesteenweg 130, 2390 Malle, Belgium**

(7) This product and any acceptable variation thereto is specified in the schedule to this certificate and the documents therein referred to.

(8) DEKRA Certification B.V., certifies that this product has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of products intended for use in potentially explosive atmospheres given in Annex II to Directive 2014/34/EU of the European Parliament and of the Council, dated 26 February 2014.

The examination and test results are recorded in confidential test report no. NL/DEK/ExTR23.0057/00.

(9) Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

EN IEC 60079-0 : 2018

EN 60079-7 : 2015 + A1 : 2018

except in respect of those requirements listed at item 18 of the Schedule.

(10) If the sign "X" is placed after the certificate number, it indicates that the product is subject to the Specific Conditions of Use specified in the schedule to this certificate.

(11) This Type Examination Certificate relates only to the design and construction of the specified product and not to the manufacturing process and its monitoring.

(12) The marking of the product shall include the following:



II 3 G

Ex ec IIC T4 Gc

Date of certification: **6 March 2024**

DEKRA Certification B.V.

R. Schuller
Certification Manager

(13) **SCHEDULE**

(14) **to Type Examination Certificate DEKRA 19ATEX0070 X**

Issue No. 1

(15) **Description**

Emergency Luminaires, Series KE2../6....-ATEX1, for fixed installation, available with several test functions, modes of operation and other options.

Ambient temperature range:

- autonomous models: -20 °C to +40 °C
- centrally supplied models: +5 °C to +40 °C

For type designation and electrical data see Annex 2 to NL/DEK/ ExTR23.0057/00.

Electrical data

See Annex 2 to NL/DEK/ExTR23.0057/00.

Installation instructions

The instructions provided with the product shall be followed in detail to assure safe operation.

(16) **Report Number**

NL/DEK/ExTR23.0057/00.

(17) **Specific conditions of use**

1. The luminaires shall be used in a location where there is low risk of mechanical danger.
2. To minimize the risk from electrostatic discharge, the luminaires shall be cleaned only with a damp cloth.

(18) **Essential Health and Safety Requirements**

Covered by the standards listed at item (9).

(19) **Test documentation**

As listed in Report No. NL/DEK/ExTR23.0057/00.